

Date	3/29/2010
Material	Fill Sand
State Pit Number	
Quarry	
Sample from stockpile at	Bay Aggregate
Pile Location	Loading Face

Sieve Size	Retained	Retained	Cumulative	Cumulative	Specification	ASTM
Sieve Size	Weight	Percent	% Retained	% Passing	Requirements	C33
2 1/2 "						
2 "						
1 1/2 "	0	0.0%	0.0%	100%		
1 1/4 "						
1 "	0	0.0%	0.0%	100%		
3/4 "	0	0.0%	0.0%	100%		
1/2 "	0	0.0%	0.0%	100%		
3/8 "	0	0.0%	0.0%	100%		
no. 4	4	0.4%	0.4%	100%		
no. 8	8	0.8%	1.2%	99%		
no. 16	12	1.2%	2.4%	98%		
no. 30	35	3.5%	5.9%	94%		
no. 50	438	43.6%	49.5%	50%		
no. 100	472	47.0%	96.5%	3%		
no. 200	33	3.3%	99.8%	0%		
pan	2	0.2%	100.0%	0%		
TOTA	AL: 1003.00	100.00%				

LOSS BY WASH	3.15%	LBW MAX		
		•		
Initial Weight	1037.1	g		
Weight after Washing	1004.4	g	Accepted	
Loss by Washing	32.7	g		
			Rejected	
MOISTURE	7.02%			
	-			
Initial Weight	1115.4	g		
Dry Weight	1037.1	g		
Moisture	78.3	g		

L Philippi Michigan Certified Aggregate Technician Cert # 101992-0213

Tested By\_\_\_\_\_